



ELO Hydraulic Valve Components Co., ...



15,875 mm x 34,925 mm x 7,14248 mm NSK
R10 JAPAN Bearing 15.875x34.925x8.73252

Bearing No. R10

R10 Bearing 2D drawings and 3D CAD models

Size	15.875x34.925x7.14248 mm
Bore Diameter	15,875 mm
Outer Diameter	34,925 mm
Width	7,14248 mm
d	15,875 mm
D	34,925 mm
B	7,14248 mm
C	7,14248 mm
r min.	0,8 mm
Weight	0,027 Kg
Basic dynamic load rating (C)	5,98534929426479 kN
Basic static load rating (C0)	3,25174200464535 kN
(Grease) Lubrication Speed	22000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.01
EAN	0029176003028
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing



ELO Hydraulic Valve Components Co., ...

Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Inch
Long Description	5/8" Bore; 1-3/8" Outside Diameter; 9/32" Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	R10
Weight / LBS	0.031
Bore	0.625 Inch 15.875 Millimeter
Outer Race Width	0.281 Inch 7.137 Millimeter
Outside Diameter	1.375 Inch 34.925 Millimeter
bore diameter:	0.6250 in
static load capacity:	728 lbs
outside diameter:	1.3750 in
precision rating:	Not Rated
overall width:	0.2813 in
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open



ELO Hydraulic Valve Components Co., ...

outer ring width:	0.2812 in
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.031 in
snap ring included:	Without Snap Ring
maximum rpm:	22000 RPM
internal clearance:	C0
series:	R
operating temperature range:	Maximum of +120 ° C
thrust application warning:	This product can not be used in Thrust Applications
dynamic load capacity:	1340 lb